


# AOV IWB-AT75F-2 Interactive WhiteBoard


## Product Specification

### Product Feature



- ✧ Front 2 USB2.0 ports
- ✧ Bottom 1 USB2.0 port only for upgrades the system
- ✧ Front 1 physical key
- ✧ Front loudspeaker
- ✧ 4K ultra HD display
- ✧ IR (Infrared Ray) touch technology
- ✧ AG tempered glass 4mm Mohs level 7
- ✧ Compatible with detachable OPS module

## Dimension



## Display

|                             |                            |
|-----------------------------|----------------------------|
| Size                        | 75 inch                    |
| Response Time               | 8ms                        |
| Aspect Ratio                | 16:9                       |
| Display Area                | 1649.664 (H)×927.936(V) mm |
| Pixel Pitch                 | 0.4296×0.4296mm            |
| Resolution                  | 3840(H)×2160(V)            |
| Refreshing Frequency        | 60Hz                       |
| Display Color               | 1.07B(10bit)               |
| Contrast Ratio              | 1200:1                     |
| Viewing Angle               | 178°(H/V)                  |
| Back Light Unit             | DLED                       |
| Brightness with glass (min) | 300cd/m <sup>2</sup>       |
| Brightness with glass (typ) | 350cd/m <sup>2</sup>       |
| Life Time                   | ≥30000 Hours               |

## Android System

|                |             |
|----------------|-------------|
| System Version | Android 8.0 |
| CPU            | A73×2+A53×2 |

|                          |   |
|--------------------------|---|
| GPU                      | Mali G51×2                                    |
| RAM                      | 2GB   |
| ROM                      | 16GB  |
| <b>Touch System</b>      |   |
| Sensing Type             | Infrared recognition                          |
| Touch point              | 20 points touch                               |
| Touch Tool               | Finger,Passive infrared pen                   |
| Minimum object size      | 3mm   |
| Response Time            | ≤10ms   |
| Accuracy                 | ±2mm  |
| Writing Height           | ≤3mm  |
| Surface Hardness         | Toughened Glass with Level 7 of Mohs Standard |
| Interpolation Resolution | 32768(W)×32768(D)                             |
| Support System           | Windows10/Windows8/Windows7/Windows XP        |
| <b>Audio</b>             |   |
| Sound Channel            | 2.0   |
| Output Power             | 2×10W   |
| <b>Power</b>             |   |
| Power Requirements       | 100-240V~ 50/60Hz 3.5A                        |
| Overall Power(Max.)      | 350W  |
| Standby Power            | ≤0.5W   |
| <b>I/O port</b>          |   |
| HDMI OUT                 | 1   |
| USB 2.0                  | 3   |
| USB 3.0                  | 3   |
| TOUCH OUT                | 2   |
| HDMI IN                  | 3   |
| VGA IN                   | 1   |
| AUDIO IN                 | 1   |

|           |   |
|-----------|---|
| RS232     | 1 |
| AUDIO OUT | 1 |
| LAN       | 1 |
| SPDIF     | 1 |

## Physical Specifications

|                                     |                  |
|-------------------------------------|------------------|
| Dimension L×H×D                     | 1709×1019×87mm   |
| Dimension (package) L×W×H           | 1860×280×1140mm  |
| Thickness of machine and wall mount | 117mm (WIB9060G) |
| Wall-hanging Screw Spec             | M8×25mm          |
| VESA                                | 800×400mm        |
| Net Weight                          | 53.05kg          |
| Gross Weight                        | 69.85kg          |

## Accessories

|   |               |
|---|---------------|
| Power Cord(European/American/Australian /British standard optional) | ×2 (3 meters) |
| USB Touch Cable (Type A-B)  | ×1 (5 meters) |
| HDMI Cable  | ×1 (3 meters) |
| Writing Pen   | ×2            |
| Remote Control  | ×1            |
| Battery   | ×2 (AAA)      |

## Environmental Conditions

|                       |                   |
|-----------------------|-------------------|
| Operation Temperature | 0℃ - 40℃          |
| Operation Humidity    | 10% - 90%RH       |
| Storage Temperature   | -20℃ -60℃         |
| Storage Humidity      | 10% - 90%RH       |
| Altitude              | Below 5000 meters |

## **Statement**

Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product.

The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance.

Should the above-mentioned change in the document become necessary, the document may be updated without written notice.